Fastener **Guide**



FASTENERS	ТҮРЕ	SIZE	LENGTH	SYSTEMS	MAKE	APPLICATIONS	USES
	Self-Tapping Hex Head (5/16")	#10, #12, #14	1/2", 3/4", 1"+, 2"+	Fencing, Gate, Guardrail, Cladding, Soffit, Decking, Screening, Battens	Hot-dipped galvanized, epoxy-coated (coarse thread)	Metal to Metal Metal to Wood	Slats to post Slats to channel Slats to gate frame Cladding/soffit/decking to metal furring/channel Battens to posts/channel/furring
	Self-Tapping Phillips Flat Head	#8, #10	1/2" +, 2-1/2"	Cladding, Soffit, Fencing, Gates, Screening (Baseplates / Mounting)	Hot-dipped galvanized, epoxy-coated (coarse thread)	Metal to Metal	Baseplates to posts Countersink cladding/soffit/decking Perpendicular batten mounting
	Self-Tapping Quadrex Flat Head	#10	1"+, 2"+	Cladding, Soffit, Decking	Hot-dipped galvanized, epoxy-coated (coarse thread)	Metal to Metal	Cladding base trims to metal channel/ girt/furring Decking to metal joist/channel/girt/ furring
	Hex Head Decking Screw	#10	1-1/2", 2"	Cladding, Soffit, Decking	Hot-dipped galvanized, epoxy-coated (coarse thread)	Metal to Wood	Cladding base trims to wood Decking to wood
	Hex Head Roofing Screw (w/ washer)	#10	1"+, 2"+	Decking, Battens	Hot-dipped galvanized, epoxy-coated (coarse thread)	Metal to Wood	Decking to wood stringer/joistBattens to wood furring/stud
	5/8" Through Bolt Hex Head + Flat Washer + Lock Nut	5/8"	10"+ (min. length 10")	Trellis, Pergola	Hot-dipped galvanized, epoxy-coated (coarse thread)	Metal to Metal	Pergola/trellis rails to posts

Fastener **Estimation Guide**



SYSTEMS	QUANTITIES
CLADDING + SOFFIT	 Trims and Starters – 10ct per stick (min. 22" oc) KEC150 – 9ct per stick (max 32" oc)
FENCE / GATES / SCREENING / GUARDRAILS	 4" and 6" Slats – 2ct per cut end 1.5" and 2.5" Slats – 1ct per cut end
DECKING	 KED150 – 14ct per stick (max. 16" oc) Finish Angle and Trims – 10ct per stick (min. 22" oc)